





# SEALAND F/M

Crane model	max. outreach m.	Outreach lifting cap. kg.		Rot. (°)	
		H1B3	H2B3		
 <b>T</b>	702T F/M 1S	10' 3"	1280	1080	370
	702T F/M 2S	15' 5"	840	710	370
	703T F/M 1S	10' 4"	2010	1700	370
	703T F/M 2S	15' 5"	1280	1080	370
	705T F/M 2S	16' 3"	1650	1410	380
	705T F/M 3S	21' 5"	1210	1040	380
	807T F/M 2S	17' 4"	2710	2310	380
	807T F/M 3S	23' 4"	1830	1570	380
	809T F/M 2S	19' 8"	2980	2540	405
	809T F/M 3S	26' 3"	2070	1760	405
	809T F/M 4S	31' 4"	1600	1370	405
	811T F/M 2S	19' 8"	3680	3130	405
	811T F/M 3S	26' 3"	2620	2230	405
	811T F/M 4S	31' 4"	2070	1760	405
	815T F/M 2S	19' 5"	5040	4280	380
	815T F/M 3S	26' 3"	3420	2910	380
	815T F/M 4S	33' 0"	2480	2120	380
	817T F/M 2S	19' 5"	5270	4480	380
	817T F/M 3S	26' 3"	3620	3060	380
	817T F/M 4S	33' 0"	2650	2250	380
 <b>A</b>	703 F/M 1S	15' 7"	1230	1060	370
	703 F/M 2S	20' 4"	890	750	370
	703 F/M 3S	25' 2"	660	570	370
	804 F/M 1S	16' 4"	1700	1440	380
	804 F/M 2S	21' 0"	1210	1030	380
	804 F/M 3S	25' 9"	900	770	380
	804 F/M 4S	30' 7"	660	560	380
	805 F/M 1S	16' 0"	1980	1690	380
	805 F/M 2S	20' 9"	1430	1210	380
	805 F/M 3S	25' 7"	1060	890	380
	805 F/M 4S	30' 4"	790	670	380
	706 F/M 1S	17' 2"	2670	2270	380
	706 F/M 2S	22' 9"	1920	1630	380
	706 F/M 3S	28' 4"	1410	1190	380
	810 F/M 1S	19' 6"	3510	2980	405
	810 F/M 2S	25' 5"	2490	2120	405
	810 F/M 3S	31' 10"	1790	1520	405
	810 F/M 4S	38' 9"	1300	1100	405
	810 F/M 5S	45' 1"	960	820	405
	812 F/M 1S	20' 2"	4210	3570	380
	812 F/M 2S	26' 7"	3000	2560	380
	812 F/M 3S	33' 4"	2200	1870	380
	812 F/M 4S	40' 1"	1610	1370	380
	812 F/M 5S	46' 11"	1200	1010	380
	815 F/M 1S	20' 2"	4940	4190	380
	815 F/M 2S	26' 7"	3530	3000	380
	815 F/M 3S	33' 4"	2600	2200	380
	815 F/M 4S	40' 1"	1940	1650	380
	815 F/M 5S	46' 11"	1340	1150	380
	817 F/M 1S	20' 5"	5560	4720	410
817 F/M 2S	26' 7"	4030	3440	410	
817 F/M 3S	33' 0"	3020	2570	410	
817 F/M 4S	39' 4"	2290	1940	410	
817 F/M 5S	46' 3"	1740	1480	410	
817 F/M 6S	53' 2"	1320	1120	410	
820 F/M 1S	20' 5"	6940	5910	410	
820 F/M 2S	26' 7"	5070	4310	410	
820 F/M 3S	33' 0"	3800	3240	410	
820 F/M 4S	39' 4"	2900	2470	410	