



817C/2S

Lbs	34390*	15810	9810	7570	5290
ft'in"	3'3"	7'1"	11'6"	14'8"	20'10"

817C/3S

Lbs	33730*	15430	9590	7340	5040	3800	2810	2120	1590
ft'in"	3'3"	7'1"	11'6"	14'8"	20'10"	27'3"	33'6"	40'4"	47'3"

817C/4S

Lbs	32630*	15170	9390	7120	4770	3530	2810	2120	1590	1260
ft'in"	3'3"	7'1"	11'6"	14'8"	20'10"	27'3"	33'6"	40'4"	47'3"	54'6"

817C/5S

Lbs	32190*	14770	8970	6790	4500	3260	2560	2120	1590	1260
ft'in"	3'3"	7'1"	11'9"	14'11"	21'1"	27'6"	33'10"	40'4"	47'3"	54'6"

817C/6S

Lbs	31530*	14550	8640	6500	4250	3030	2310	1870	1590	1260
ft'in"	3'3"	7'1"	12'0"	15'2"	21'4"	27'9"	34'1"	40'8"	47'3"	54'6"

*) Portata teorica - Theoretical lifting capacity

C= Retractable jib, for high load application

MODELLI MODELS	MOMENTO LIFTING MOMENT	SBRACCIO ORIZ. HORIZ. EXTENSION	PORTATA AL MAX. SBRACCIO MAX. REACH LIFTING CAPACITY	ANGOLO DI ROTAZIONE SLEWING ANGLE	PESO WEIGHT	DIMENSIONE DIMENSION
	ft Lbs	ft'in"	Lbs	°	Lbs	inches WxHxD
817C/2s	112800	20'10"	5290	380	4850	98x91x39
817C/3s	-	27'3"	3800	380	5110	98x91x40
817C/4s	-	33'6"	2810	380	5380	98x91x40
817C/5s	-	40'4"	2120	380	5600	98x91x40
817C/6s	-	47'3"	1590	380	5800	99x91x40