



RADIO REMOTE STANDARD

Model	Lbs	21340*	9740	5200	3660				
911/1S	ft'in"	3'3"	7'3"	13'9"	19'6"				
911/2S	Lbs	20860*	9480	4980	3450	2620	1910	1400	1050
	ft'in"	3'3"	7'3"	13'9"	19'6"	25'5"	31'10"	38'9"	45'7"
911/3S	Lbs	20130*	9150	4670	3170	2430	1910	1400	1050
	ft'in"	3'3"	7'3"	14'1"	19'10"	25'9"	31'10"	38'9"	45'7"
911/4S	Lbs	19400*	8820	4400	2950	2170	1730	1400	1050
	ft'in"	3'3"	7'3"	14'5"	20'2"	26'1"	32'2"	38'9"	45'7"
911/5S	Lbs	18290*	8310	4160	2740	1970	1520	1230	1050
	ft'in"	3'3"	7'3"	14'8"	20'6"	26'5"	32'6"	38'7"	45'1"

*) Portata teorica - Theoretical lifting capacity

MODELLI MODELS	MOMENTO LIFTING MOMENT	SBRACCIO ORIZ. HORIZ. EXTENSION	PORTATA AL MAX. SBRACCIO MAX. REACH LIFTING CAPACITY	ANGOLO DI ROTAZIONE SLEWING ANGLE	PESO WEIGHT	DIMENSIONE DIMENSION
	ft Lbs	ft'in"	Lbs	°	Lbs	inches WxHxD
911/1s	71600	19'6"	3660	405	2730	98x86x26
911/2s	-	25'5"	2620	405	2910	98x86x26
911/3s	-	31'10"	1910	405	3130	98x86x26
911/4s	-	38'9"	1400	405	3330	98x86x26
911/5s	-	45'1"	1050	405	3480	98x86x30